





BTA-JAG97CD

AUDIO STREAMING INSTALLATION GUIDE FOR SELECT 1986-97 JAGUAR <u>WITH CD CHANGER</u>

Created August 16, 2024 Revised: September 13, 2024

PRODUCT SAFETY & DISCLAIMER

READ ALL INSTRUCTIONS CAREFULLY BEFORE INSTALLING, FAILURE TO DO SO MAY CAUSE PERSONAL INJURY OR DAMAGE TO PRODUCT AND/OR PROPERTY

- This installation guide is provided as a GENERAL installation guide, some vehicles vary and
 may require additional steps. We do not accept responsibility for third party labor charges
 or modifications. Exercise due-diligence when installing this product.
- We do not accept any responsibility for vehicle damage or personal injury resulting from the installation of this product.
- Careless installation and operation can result in equipment damage.

Requirements 1987-97 Jaguar with CD changer

Introduction

Portable audio products are everywhere, reflecting demand from active people all over the world to take their music on the road. The new BTA-JAG97CD (formerly A2D-JAG97) provides Bluetooth audio streaming solution from any A2DP enabled device to allow Jaguar owners to stream audio books, Apple music, Deezer, turn by turn directions, USB charging (5V/2A) and CD changer retention. For the BTA-JAG97CD to work, vehicle must have a fully functioning CD changer which remain connected and operational. If vehicle does not have a functioning CD changer, purchase our BT3-JAG97 instead. makes it easier to use the integrated USB charging port. See installation 1 for details.

See Frequently Asked question at the end of this guide for more details.

Installation: To radio

Warning: The BTA-JAG97CD requires and retains the 6-disc <u>CD changer</u>. If vehicle does not have a CD changer or if it malfunctions; this module will NOT work.

Click <u>here</u> to remove radio or click link below for dash removal instruction video. XK models differ slightly. https://www.youtube.com/watch?v=vpAldr6V3iE

- Disconnect factory CD plug (See Fig. 1) from radio "CD" socket (See Fig. 2)
- 2. Connect factory CD plug to 8-pin socket on harness (See Fig. 3)



Fig. 1



Fig. 2

3. Connect 8-pin male plug from harness (See Fig. 1) to the 8-pin socket on radio vacated in step 1 (See Fig. 2)



Fig. 3

 Connect/splice or tap red Accessory wire (See Fig. 4) to vehicles 12V accessory (switched) supply. 5. 12V accessory is available on radio main harness (plug) @ pin 9 (Light green/orange). Use voltmeter to test light to verify voltage condition prior to finalizing install.

Do not connect accessory wire to 12V battery (always on)



Fig. 4

6. Connect installation harness 16-pin plug (See **Fig. 6**) to module 16-pin socket (See **Fig. 7**)



Fig, 5 16-pin plug



Fig. 6 16-pin socket

USB charging port

The BTA-JAG97 module includes a USB charging port (See **Fig. 7**) rated 5V/2A charging current. If you decide to use it, simply plug in the USB charging cable for your device or purchase our dash mount USB extension cable seen in **Fig. 8** and available here.

Note: The USB port is for charging only.



Fig. 7




Fig. 8 optional dash mount extension cable

Pairing

Pairing process varies among devices but basic steps are the same. This process is done upon initial install and will not have to be repeated.

- 1. Turn ignition and radio "ON"
- 2. Go to device: Settings, Wireless & Networks, Bluetooth Settings
- 3. Select *Bluetooth* and turn it "ON" (if not already ON).
- 4. Tap **Scan for devices**.
- 5. Wait for Bluetooth device name to appear (See below) and tap.



Note: It is possible to pair multiple devices, but only one connection is supported. Pairs automatically with device to which it connected last.

Bluetooth operation

- 1. Turn ignition and radio "ON"
- 2. Ensure there is at least one "DISC" in CD changer magazine
- 3. Press "TAPE/CD" button on radio.
- 3. Launch streaming application on audio device
- 4. Launch audio device streaming application.
- 5. Set smartphone volume to zero
- 6. Turn radio volume up 75% (3/4)
- 7. Increase smartphone volume until audio begins to distort then decrease sightly until distortion free.
- 8. Use included wireless remote or device built-in controls to change tracks, adjust device volume, pause etc. (See **Fig. 9**)



- 9. To switch over to the CD changer, press remote Pause/Play button.
- To switch back to streaming, press remote Pause/Play button.
- 11. If correct operation is confirmed, tuck away any extra wires and enjoy!

Frequent ask questions & troubleshooting

- My vehicle has a functioning CD changer. Can I keep it and also be able to stream from smartphone?
 - **YES**; if the CD changer in trunk or hatch is <u>functional</u>, the BTA-JAG97CD is able to provide a streaming and retains use of the **CD changer**.
- 2. I notice both your BTA-JAG97CD and BTA-JAG98 list compatibility with 1997 XK. What's the difference and which should I purchase? Jaguar introduced an updated audio system in late 1997 XK8 which means vehicles in the same calendar year will have different audio systems (connectors/plugs). If you own a late 1997 XK8, please inspect the CD plug: Fig. 10. Ai-NET (right) applies to late 1997 XK8 and fits our BTA-JAG98 Older vehicles including early 1997 XK8 with 8-pin DIN plug (left) fits the BTA-JAG97CD

Avoid costly returns by inspecting the CD plug in your vehicle prior to ordering



Fig. 10 8-pin DIN plug (left) applies to early 1997 XK8

- 3. How do I switch between streaming and CD playback?
 The module automatically switches to CD when not paired. To switch between streaming and CD or vice versa; press PAUSE/PLAY button on remote control or audio device touch screen.
- 4. Can I connect the BTA-JAG97CD module directly to the radio? YES; The BTA-JAG97CD connects to the radio.

- Can I control smartphone playback from radio buttons?
 NO; you must use smart device built-in controls to access music files. A safer less distracting option is to use the remote control (See Fig. 9) which includes most used functions (e.g., track up/down, pause/play and volume.)
- 6. I've installed module, but my phone does is unable to find DisCarSt.

 Ensure ignition key is in ACC or ON positions and also the RED accessory wire is connected to a 12V Accessory supply. Follow installation 3 on page 3.
- What is the difference between the BT3-JAG97, BTH-JAG97CD and BTA-JAG97CD?

The BT3-JAG97 works in vehicles <u>without CD changer</u> or if CD changer is no longer wanted (disconnected) to provide Hands-free calling, streaming and USB charging.

The <u>BTH-JAG97CD</u> works only in vehicles <u>with a functioning 6-disc CD</u> <u>changer</u> in trunk/hatch. CD changer remains connected and functional to provide Hands-free calling, streaming and USB charging. (See Fig. 11)

The <u>BTA-JAG97CD</u> works only in **vehicles with a functioning 6-disc CD changer** in trunk/hatch. CD changer remains connected and functional to provide Streaming and USB charging (See Fig. 11)



Fig. 11 required CD changer

Disclaimer

- This product has no affiliation with Jaguar
- We're not liable for misuse of this product.
- •Whenever possible professional installation is recommended.

For additional questions email $\underline{\text{support}} \underline{\text{adiscountcarstereo.com}}$

© 1995- Sep-24 Discount Car Stereo. All rights reserved. Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.